

MSDS MATERIAL SAFETY DATA SHEET

Oakwood Products, Inc
1741 Old Dunbar Road
West Columbia, SC 29172
www.oakwoodchemical.com

Phone Numbers:

Product Information	803-739-8800
Transportation Emergency	800-451-8346
Outside the USA	760-602-8700

MATERIAL IDENTIFICATION

NAME: 3-Chloro-4-fluorophenyl isothiocyanate
CAS#: [137724-66-4]
CAT#: 8759
For R&D use only.

HEALTH HAZARD INFORMATION

LACHRYMATOR
CORROSIVE
TOXIC

Harmful to skin, eyes, and respiratory system.

Toxic if swallowed.

Avoid prolonged exposure.

Do not breathe vapor.

Use caution when handling.

Exposure to any chemical should be limited.

To the best of our knowledge, the health hazards of this material have not been fully investigated.

Material is for research and development purposes only.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Avoid all direct contact with product.

Wear protective safety goggles.

Wear chemical-resistant gloves.

Wear protective clothing and boots.

Ensure ventilation during use.

After contact with skin, wash immediately.

FIRST AID

EYE CONTACT: Check for and remove any contact lenses. IMMEDIATELY flush eyes with running water for at least 15 minutes while keeping eyes open. COLD water may be used. Seek medical attention.

SKIN CONTACT: After contact with skin, wash with plenty of water. Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. COLD water may be used. Cover the irritated skin with an emollient. Seek medical attention. Wash any contaminated clothing before reusing.

INHALATION: Remove victim from source of exposure to fresh air. If breathing is difficult administer oxygen. Seek medical attention.

INGESTION: Do not induce vomiting. Give water to victim to drink. Seek medical attention.

FIRE MEASURES

Extinguishing media: carbon dioxide, dry chemical powder, alcohol or polymer foam.
Special fire-fighting procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.
Unusual fire and explosion hazards/decomposition of product: emits toxic fumes under fire conditions.

HANDLING AND STORAGE INFORMATION

LACHRYMATOR
CORROSIVE
TOXIC
AVOID PROLONGED USE
AVOID ALL DIRECT CONTACT WITH MATERIAL
Wash thoroughly after handling.
Do not breathe dust or vapor.
Have safety shower and eye wash available.
Do not get in eyes, on skin, on clothing.
Keep container tightly closed.
Store in a cool, dry, well-ventilated area.
Ensure adequate ventilation during use.
Use only in a chemical fume hood.
Avoid sources of ignition.

ACCIDENTAL RELEASE MEASURES

Steps to be taken if material is released or spilled: Wear appropriate respirator, rubber boots and heavy rubber gloves. Scoop up and place in an appropriate container. Ventilate area and wash spill site after pickup is complete. Wash skin immediately with plenty of water. Absorb on sand or vermiculite and place in closed containers for disposal.

DISPOSAL INFORMATION

Dissolve in or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber. Observe all Federal, State and local laws.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: clear, yellow liquid
MF: C₇H₃ClFNS
MW: 187.62
BP: 82°C/1mm Hg
MP: no data
DEN: no data
N_d²⁰: no data
FP: no data

Oakwood Products, Inc
1741 Old Dunbar Road
West Columbia, SC 29172
Phone: (803) 739-8800
Fax: (803) 739-6957

3-Chloro-4-fluorophenyl isothiocyanate
June 11, 2009

REACTIVITY DATA

INCOMPATIBILITIES: strong oxidizing agents, strong acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: may evolve carbon monoxide, carbon dioxide, nitrogen oxides, sulfur oxides, hydrogen chloride, and hydrogen fluoride.

TOXICITY INFORMATION

ACUTE EFFECTS:

Corrosive

Toxic

May be harmful by ingestion and inhalation.

Material is irritating to mucous membranes and upper respiratory tract.

To the best of our knowledge, the toxicological properties of this product have not been fully determined.

TRANSPORT INFORMATION

Corrosive liquids, toxic, n.o.s.

8, 6.1

UN2922 III

The above information is believed to be correct but does not purport to be all-inclusive and shall be used only as a guide. Oakwood shall not be held liable for any damage resulting from handling or from contact with the above product.